


# TECHNICAL DATA KÄHR'S LUXURY TILES



**Click Stone** 300 x 600 x 6 x 0.55 mm  
1.8 m<sup>2</sup>/box, 48 box/pallet






**Click Wood** 218 x 1210 x 6 x 0.55 mm  
2.112 m<sup>2</sup>/box, 40 box/pallet

## PRODUCT












Click LVT Rigid Core SPC+ IXPE	EN ISO 10582	Luxury Vinyl Tile
Joint		Click 5G
Application	EN ISO 10874	23/33/42



## SPECIFICATION

Thickness		EN ISO 24337	6.0 mm
Weight		EN ISO 24342	9.76 kg/m <sup>2</sup>
Wear layer		EN ISO 24346	0.55 mm

## PRODUCT PROPERTIES

PROPERTY	TEST METHOD	RESULT
Indoor air certifications		M1, FloorScore, A+
Fire resistance	 EN 13501-1	Bfl-s1
Residual indentation	 EN ISO 24343-1 (2,5 h)	< 0.2 mm (*with underlayment)
Dimensional stability	 EN ISO 23999 (80 °C/6 h)	< 0.1 %
Colour fastness	 EN ISO 105-B02	≥ 6
Slip resistance	 EN 13893 DIN 51130	DS (> 0.3) R10
Electrical propensity	 EN 1815	< 2 kV (antistatic)
Wear and scratch resistance	 EN 16094	Pass with good results
Chemical resistance	 EN ISO 26987	Pass with good results
Effect of castor chair	 EN 425	Suitable
Underfloor heating		Ok (max +27 °C)
Bacterial growth		Does not act as substrate
Impact sound reduction	 EN ISO 10140	20 ΔL <sub>w</sub> dB (IXPE underlayment)

Cleaning and maintenance instructions, see: [www.kahrsflooring.com/www.kahrs.com](http://www.kahrsflooring.com/www.kahrs.com)

