



Art	E-nr	Färg	RAL
1291AL	7748047	ALUMINIUM	9006
1291GR	7748048	GRAFIT	7016

## Allmän information

Typ armatur	Pollare
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	PMMA, klart
Typ ljuskälla	LED modul + driver
Ljusstyrning	Dimbar (Triac)
Netto / Bruttovikt armatur	3,51kg / 4,24kg
Förpackning mått [cm]	15,5x15,5x55
LED	Cree DK210704 V2 JB2835 3V 3K (⊗ Produktblad)
Drivdon	TCI MICRO MD 10W 350mA 127040 Triac (⊗ Produktblad)
Led modul effekt	7,4W
Armatur effekt	9,1W
Lumen modul	1370lm
Lumen ut	864lm
Led modul effekt	185,1lm/W
Armaturens effekt	94,9lm/W
Färgtemperatur	3000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	>72 000h
Energieffektivitetsindex (EEI)	A <sub>3</sub> C / ⊗ EPREL
Effektfaktor	PF 0,90
THD-faktor	10%
Ta nominel:	+25°C
Inrush current	2A / 50µs

## Filer som kan laddas ned

Photometric LDT files, Photometric IES files, Manualer, BIM Revit, BIM ArchiCAD