


Art.nr	El.nummer	Farge	RAL
1314AL	3102468	ALUMINIUM	9006
1314GR	3102469	GRAFITT	7016
1314B	3104144	SORT	9005

Generell informasjon	
Type armatur	Pullert
Materiale	Pulver lakkert aluminiumstøp
Lysstyring	Faseavsnitt
Netto / Brutto vekt armatur	4,5kg / 4,85kg
Forpakkingsstørrelse [cm]	22,3x12,8x87
Driver	Philips Xitanium 10W 0,5A 20V TE SC 230V (⚡ Produktblad/FDV)
Effekt W	5,8W
Armatureffekt	7,7W
Modul lumen	828lm
Lumen ut	697lm
Modul effektivitet	142,8lm/W
Armatur Lumen/Watt	90,5lm/W
ULOR	1%
Fargetemperatur	3000K
Farvekonsistens (McAdam-Ellipse)	SDCM3
Fargegjengivelsesindeks	80
Beregnet levetid L70/B50 ved 25°C	>109 000h
LED fotobiologisk trussel	RG0 or RG1
Energieffektivitetsindeks (EEI)	 / ⚡ EPREL
Virkningsgrad	PF > 0,95
THD-faktor	< 20%
Ta nominel:	+25°C
Maksimal omgivelsestemperatur	+40°C
Inrush current	3,36A/36µs

## Filer som kan lastes ned

Photometric LDT files, Photometric IES files, Manual, BIM Revit, BIM ArchiCAD