Ocean 8 XL. Technical data.



03/2023

	contains	m²	ft²	weight
1 pack Ocean 8 XL	6 planks	2,95 m ²	31.72 ft ²	21,1 kg
1 pallet Ocean 8 XL	54 packs	159,14 m²	1712.92 ft ²	1159 kg



product specifications

Dimensions	2038 x 241 mm	
Total thickness	8 mm	
Bevels	4	
Loc System	PentaLoc	
Level of use according to European standard EN10874	23 heavy domestic use	
	32 general commercial use	
Residential warranty	lifetime	
Commercial warranty	5 years	

Warranty conditions on www.berryalloc.com.

composition

Surface layer	Direct laminated paper, impregnated with melamine resin.	
Substrate	Moisture resistant High Density Fiberboard (HDF) treated with hydro+ water repelling technology.	
Backing	Direct laminated paper, impregnated with melamine resin.	

test results

Abrasion resistance	EN13329	AC4 (IP≥4000)
Impact resistance	EN13329	small ball : ≥ 35 mm - big ball : ≥ 750 mm
Thickness swelling	ISO 24336	12% (requirement ≤ 18%)
Water resistance	ISO 4760	up to 24 hours
Fire resistance	EN13501-1	Cfl-S1
Formaldehyde emission	EN717-1	E1
Slip resistance	EN13893	DS
Density	EN323	900 kg/m³
Resistance to staining	EN438	5 (groups 1+2) ; 4 (group 3)
Effect of a furniture leg	EN16581	no damage (foot type 0)
Effect of a castor chair	EN425	no damage with type W wheels
Thermal resistance in combination with ISO 8302 underlay Excellence Plus		0,08 m ² K/W – Suitable for floor heating/cooling. Detailed instructions on www.berryalloc.com.










laminate.

Ocean 8 XL. Technical data.



03/2023

What is a laminate floor made of?



- An **overlay** that determines the strength and resistance of your floor
- 2 A decor paper for the design
- 3 A high-density fibreboard (HDF) core
- **4** A **counterbalance** to stabilise and protect the HDF core
- **5** The **hydro+** water-repellent coating*

(*) Only available for our Ocean+ collections