Ocean 8 V4. Technical data.



03/2023

	contains	m²	ft²	weight
1 pack Ocean 8 V4	9 planks	2,20 m ²	23.71 ft ²	15,7 kg
1 pallet Ocean 8 V4	56 packs	123,34 m ²	1327.61 ft ²	891 kg



product specifications

Dimensions	1288 x 190 mm	
Total thickness	8 mm	
Bevels	4	
Loc System	DuoLoc	
Level of use according to European standard EN10874	23 heavy domestic use	
	32 general commercial use	
Residential warranty	lifetime	
Commercial warranty	5 years	

Warranty conditions on www.berryalloc.com.

composition

Surface layer	Direct laminated paper, impregnated with melamine resin.	
Substrate	Moisture resistant High Density Fiberboard (HDF) treated with hydro+ water repelling technology.	
Backing	Direct laminated paper, impregnated with melamine resin.	

test results

Abrasion resistance	EN13329	AC4 (IP≥4000)	
Impact resistance	EN13329	small ball : ≥ 35 mm - big ball : ≥ 750 mm	
Thickness swelling	ISO 24336	12% (requirement ≤ 18%)	
Water resistance	ISO 4760	up to 24 hours	
Fire resistance	EN13501-1	Cfl-S1	
Formaldehyde emission	EN717-1	E1	
Slip resistance	EN13893	DS	
Density	EN323	900 kg/m³	
Resistance to staining	EN438	5 (groups 1+2) ; 4 (group 3)	
Effect of a furniture leg	EN16581	no damage (foot type 0)	
Effect of a castor chair	EN425	no damage with type W wheels	
Thermal resistance in combination with ISO 8302 underlay Excellence Plus		0,08 m ² K/W – Suitable for floor heating/cooling. Detailed instructions on www.berryalloc.com.	










laminate.

Ocean 8 V4. Technical data.



03/2023

What is a laminate floor made of?



- An **overlay** that determines the strength and resistance of your floor
- 2 A decor paper for the design
- 3 A high-density fibreboard (HDF) core
- **4** A **counterbalance** to stabilise and protect the HDF core
- **5** The **hydro+** water-repellent coating*

(*) Only available for our Ocean+ collections