

TECHNICAL DATA SHEET

Pergo Lofoten

Edition 11.2016



General data

Panel	1 strip	1820 x 190 mm
Total thickness		12,5 mm
Numbers of panels per pack		6
m ² per pack		2,0750 m ²

Panel build up

Toplayer	PEFC controlled sources	2,5 mm
Core board		HDF Mastercore
Backing layer	PEFC controlled sources	Spruce or Pine
Tongue and groove	Length	Uniclic
	Width	Perfect fold 3.0

Surface layer

Wood species	Oak
Origine	Europe
Finishing	Extra Matt / Matt lacquer

Installation

Floating	On Pergo underlay	CF installation instructions
Glued to subfloor	Pergo MS polymere resin	CF installation instructions

Warranty

Domestic use	Conditions in each pack	25 years
Uniclic connection		Lifetime
Commercial		On request

Finishing

UV curing varnish		5 - 7 layers	
Wear resistance	SIS 923509	Falling sand	800 - 1000
	DIN 68861	S 33	100 - 1050
Scratch resistance		Anti-scratch top coat	
Stain resistance	EN 13442	All except blue ink	class 5
		Blue ink	class 3
CE	EN 14342: 2008-09		DOP PCO 0501
Castor chairs		Use soft castors, type W (EN 12529) and/or suitable office mat	
Slip resistance	CEN/TS 15676		USRV 50-52
Emission of formaldehyde	EN 717-1		E1
PCP			below detection limit
Heat resistance	EN 12664		0,121 m ² K/W
Underfloor heating	Suitable	CF special installation instructions	
Reaction to fire	EN 14342	CWFT	CI-s1

Ecological certificates

U-zeichen	Z 156.606-898
AFFSET	A+
Nordic ecolabel	3029-0001
PEFC	PEFC/07-32-37
M1	OK
EPD	On request



