

**Product Information**

Product	Three-layer parquet, 14 mm, Oak
Use	Floor covering for indoor use
Manufacturer	Bjelin d.o.o. Žegar VI/39, Ogulin
Standards applicable	HRN EN 14342:2013 - Wood flooring

**Technical data**

Dimensions	14 mm	HRN EN 13489;
Density	710kg/m <sup>3</sup>	HRN EN 13489;
Breaking strength	2000	HRN EN 13696; HRN EN 14354;
Thermal conductivity	0,10 m <sup>2</sup> K/W	HRN EN 14342:2013
Biological durability	2/S/M	HRN EN 14342:2013
Reaction to fire	Cfl-s1	HRN EN 14342:2013
Formaldehyde emission	E1	HRN EN 14342:2013
Content of pentachlorophenol	<5ppm	HRN EN 14342:2013
Slipperiness	50 USRV	HRN CEN/TS 15676:2010

**Installation**

Installation method	Floating installation, Välinge 2G/5G®
Installation instruction	Download from <a href="http://www.bjelin.com/installation">www.bjelin.com/installation</a>
Under floor heating compatible	Maximal floor surface temperature 27°C
Underlayment material	Foam with CS ≥ 60 kPa & CC ≥ 5 kPa

The product CE label marking characteristics, which are described in **EN 14342:2013**